



Medium Duty Diesel



SET #



ENGINE



APPLICATION



MFG



YEARS



CC



GROOVE



BORE



SIZE



MATERIALS

SET #	ENGINE	APPLICATION	MFG	YEARS	CC	GROOVE	BORE	SIZE	MATERIALS
2D5374	VT 365 363 cu. in	6.0L Turbo International Power Stroke Special .055 to .065 gap 2nd rings	FORD	2003-10		2.25 2.00 3.50	95.00	Std, 25, 50 75, 100	Ductile Ceramic Chrome UCR, Carbodic Grey LCR, 2pc Cast OCR
2D5741	391 cu. in.	6.4L Turbo Power Stroke 32V Vin. R	FORD			2.50 2.00 3.00	98.20	Std, 25 50, 75	Ductile Ceramic Chrome UCR, Carbodic Grey LCR, 2pc Cast OCR
2D5853	406 cu. in	6.7L Turbo OHV Direct Injection Power Stroke 32V Vin T	FORD	2011-14		3.00 2.00 2.50	99.00	Std, 25, 50 75, 100	Ductile Ceramic Chrome UCR, Carbodic Grey Napier LCR, 2pc Nitride OCR
2D4914	6B, 6BT 6BTA 6BT ISB	Turbo diesel 12 valve 5.9 Litre 359cu. in. 5.9L Vin; C,D.8 12v Turbo Intercooled Cummins Pickup, Ram 5.9L F650, F750 5.9L OE Ref. 3802421 sups 3802230	CUMMINS DODGE DODGE FORD	 1988-97 1998-04 2004-07	5899cc 5899cc 5899cc	3.00 2.35 4.00	102.00	Std, 50 75, 100	Ductile Ceramic Chrome UCR, Carbodic Grey LCR, 2pc Cast OCR
2D7276	BT 4BT 6BT 6BTA5.9	180 cu. in. 2.9L OEM 3802230 239 cu. in 3.9L OEM 3802230 359 cu. in. 5.9L OEM 3802230 359 cu. In. 5.9L (turbo Cummins) Vin C, D, 6, 7, 8,	CUMMINS CUMMINS CUMMINS DODGE			3.00 2.39 4.00	102.00	Std, 50 100	Ductile Ceramic Chrome UCR, Carbodic Grey LCR, 2pc Cast OCR
2D4845	LBZ LGH LML LMM LB7 LLY	Cutaway , Express, Alpha, Savana G2500, G3500 6.6L DURAMAX Cutaway, Express , Alpha, Savana G2500, G3500 6.6L DURAMAX Cutawa, Express, Alpha, Savana G2500, G3500 6.6L DURAMAX Cutaway, Express, Alpha, Savana G2500, G3500 6.6L DURAMAX Sierra 2500, Silverado, Topkick 6.6L DURAMAX Sierra 2500, Silverado, Topkick 6.6L DURAMAX	GM	2006-07 2010-11 2011-16 2008-09 2001-04 2004-05	6599cc 6599cc 6599cc 6599cc 6599cc 6599cc	3.00 2.00 3.00	103.00	Std, 50 100	Nitride UCR, Ductile Scraper Chrome LCR, 2pc Nitride OCR
2D4744	395cu. in. 396cu. in.	Vin: F,S,Y Diesel Turbo 6.5L Hummer Diesel Turbo Special .029 to .039 gap 2nd ring	GM	1992-06 1992-06		3.00 2.00 4.00	103.00	Std, 50, 75 100, 150	Ductile Ceramic Chrome UCR, Carbodic Grey LCR, 2pc Cast OCR
2D4882	445 cu. in.	7.3L Navistar Turbo, Direct Injection, Power Stroke Spec .062 to .072 gap 2nd ring	FORD	1994-04		3.00 2.00 3.50	104.40	Std, 25 50, 75, 100	Ductile Inlaid Ceramic Chrome UCR, Carbodic Grey LCR, 2pc Cast OCR